

BMW CCA, Los Angeles Chapter 2011 Autocross Classifications

4C	ALL 4 cylinder BMW models
6S	Stock 6-8-12 cylinder BMWs up to 295 stock hp
6M	Modified 6-8-12 cylinder BMWs up to 295 stock hp
TS	Stock 6-8-12 cylinder BMWs over 295 hp, M cars before 1994
TM	Modified 6-8-12 cylinder BMWs over 295 hp, M cars before 1994
MS	Stock M models 1994 - present
MM	Modified M models 1994 - present
MC	ALL R-class MINI Cooper models
X	ALL non-BMW or non-MINI models
G	ALL Instructors OR drivers who opt into Gold Class AND drivers running non-DOT tires (i.e. slicks)

Modifications Permitted in Stock Classes:

- ANY size wheel and tires. Tires must be DOT treadwear rating of 140 or higher
- ANY shock absorber using stock mounting and ANY suspension bushing material
- ANY air filter or air intake AHEAD OF mass airflow meter
- Software/firmware alterations are permitted on naturally-aspirated engines only
- ANY brake pad material allowed with Stock-size brake components
- Catalyst-back exhaust systems and strut tower braces are permitted

ANY other alterations are Modified Classes, including:

- Tires with DOT treadwear rating under 140
- Non-stock springs, coilover suspensions, anti-roll bars
- Software/firmware alterations to turbocharged/supercharged engines
- Non-stock mass airflow meters, camshafts, downpipes, removed catalytic converter
- Non-stock-size brake rotors or calipers (stock-size replacements OK in Stock)